

**IN THE CLAIMS:**

The following listing of claims will replace all prior listings of claims in the application:

1. (Original) A dedicated, hardware-based Physics Processing Unit (PPU), comprising:
  - a vector processor adapted to perform multiple, parallel floating point operations to generate physics data; and
  - a data communication circuit adapted to communicate the physics data to a host.
2. (Original) The PPU of claim 1, wherein the host comprises a Central Processing Unit (CPU), and the PPU further comprises:
  - a PPU Control Engine (PCE) receiving commands from the CPU and controlling communication the physics data from the PPU to the host.
3. (Original) The PPU of claim 2, wherein the PPU further comprises:
  - an external memory and an internal memory; and
  - a Data Movement Engine (DME) controlling the movement of data between the external memory and the internal memory in response to instructions received from the PCE.
4. (Original) The PPU of claim 3, further comprising:
  - a Floating Point Engine (FPE) performing multiple, parallel floating point operations on data stored in the internal memory.
5. (Original) The PPU of claim 4, wherein the internal memory is operatively connected to the DME, and further comprising:
  - a high-speed memory bus operatively connecting an external high-speed memory to at least one of the DME and the FPE.

6. (Original) The PPU of claim 5, wherein the internal memory comprises multiple banks allowing multiple data threading operations.

7. (Original) The PPU of claim 3, wherein the PCE comprises control and communication software stored in a RISC core.

8. (Original) The PPU of claim 5, wherein the internal memory comprises first and second banks, and wherein the DME further comprises:

a first unidirectional crossbar connected to the first bank;  
a second unidirectional crossbar connected to the second bank; and,  
a bi-directional crossbar connecting first and second crossbars to the external high-speed memory.

9. (Currently Amended) ~~A dedicated, hardware-based Physics Processing Unit (PPU) connected within a system, to a Central Processing Unit (CPU) and comprising:~~

~~a Central Processing Unit (CPU);  
an external memory storing data; and,~~  
~~a dedicated, hardware-based Physics Processing Unit (PPU) connected to the CPU and comprising~~ an Application Specific Integrated Circuit (ASIC)  
implementing a vector processor adapted to perform multiple, floating point operations; and  
~~an external memory storing data, wherein the external memory is communicatively coupled to the PPU.~~

10. (Currently Amended) ~~The PPU system of claim 9, wherein the system comprises further comprising~~ a Personal Computer (PC); and wherein the PPU comprises an expansion board adapted for incorporation within the PC, the expansion board mounting the ASIC and the external memory.

11. (Currently Amended) The PPU system of claim 10, further comprising circuitry enabling at least one data communications protocol between the PPU and CPU.

12. (Currently Amended) The PPU system of claim 11, wherein the at least one data communications protocol comprises at least one protocol selected from a group of protocols defined by USB, USB2, Firewire, PCI, PCI-X, PCI-Express, and Ethernet.

13. (Currently Amended) The PPU system of claim 11, wherein the ASIC comprises a PPU Control Engine (PCE) receiving commands from the CPU and controlling data communications between the PPU and PC.

14. (Currently Amended) The PPU system of claim 13, wherein the ASIC further comprises:

an internal memory; and  
a Data Movement Engine (DME) controlling the movement of data between the external memory and the internal memory in response to instructions received from the PCE.

15. (Currently Amended) The PPU system of claim 14, further comprising:  
a Floating Point Engine (FPE) performing multiple, parallel floating point operations on data stored in the internal memory.

16. (Currently Amended) The PPU system of claim 15, wherein the internal memory is operatively connected to the DME, and further comprising:  
a high-speed memory bus operatively connecting the external memory to at least one of the DME and the FPE.

17. (Currently Amended) The PPU system of claim 16, wherein the internal memory comprises multiple banks allowing multiple data threading operations.

18. (Currently Amended) The PPU system of claim 17, wherein the internal memory further comprises:

an Inter-Engine memory transferring data between the DME and FPE.

19. (Currently Amended) The PPU system of claim 18, wherein the internal memory further comprises:

a Scratch Pad memory.

20. (Currently Amended) The PPU system of claim 14, further comprising a command packet queue transferring command packets from the PCE to the DME.

21. (Currently Amended) The PPU system of claim 15, wherein the FPE comprises a plurality of Vector Floating-point Units.

22. (Currently Amended) The PPU system of claim 21, wherein at least one of the command packets defines a vector length of variable length.

23. (Currently Amended) The PPU system of claim 15, wherein the DME comprises a plurality of Memory Control Units (MCUs) and a Switch Fabric connecting the MCUs to the external memory; and,

wherein the FPE comprises a plurality of Vector Processing Engines (VPEs) receiving date from at least one of the MCUs via a VPE bus.

24. (Currently Amended) The PPU system of claim 23, wherein each Vector Processing Engine (VPE) comprises a plurality of Vector Processing Units (VPUs) receiving data from the VPE bus.

25. (Currently Amended) The PPU system of claim 24, wherein each VPU comprises:

a dual bank[[.]] Inter-Engine Memory (IEM) receiving data from the VPE bus;

one or more data registers receiving data from the IEM under the control of an associated Load/Store Unit; and  
an Execution Unit performing parallel floating point operations.

26. (Currently Amended) The PPU system of claim 23, wherein at least one command packet received from the PCE defines a vector length of variable length.

27. (Currently Amended) The PPU system of claim 23, wherein the Switch Fabric comprises at least one crossbar circuit.

28. (Currently Amended) The PPU system of claim 24, wherein each VPU is dynamically re-configurable.